

INDUSTRIAL TUMBLE DRYERS



GZZ15D GZZ30D

GZZ50D GZZ70D

GZZ100D

GDZ15D GDZ30D

GDZ50D



FEATURES:

- High quality stainless steel basket
- Double belts drive system with high quality belts
- Efficient airflow system with large basket perforation
- Large and powerful heat exchanger for quick drying process
- Special design fan impeller provides large air flow and less maintenance
- Drawer type lint filter for easy cleaning*
- Programmable computer controller with maximum 5 programs
- Safety switch to stop machine when door opens
- Oversize loading door with large sight glass
- Standard powder coated steel panels
- Reversible basket*
- Optional cool air bypass system*
- Optional Stainless steel front and side panels*

* except GZZ15D and GDZ15D

TECHNICAL DATA

	UNIT	GZZ15D	GZZ30D	GZZ50D	GZZ70D	GZZ100D	GDZ15D	GDZ30D	GDZ50D
Capacity	KG	15	30	50	70	100	15	30	50
Heating Mode		Steam	Steam	Steam	Steam	Steam	Electric	Electric	Electric
DRUM									
Diameter	mm	800	940	1150	1270	1450	800	940	1150
Depth	mm	640	930	970	1120	1250	640	930	970
Volume	L	322	645	1008	1419	2065	322	645	1008
Rotation Speed	RPM	38	35	32	30	28	38	35	32
LOADING DOOR									
Door Opening	mm	610	610	820	820	820	610	610	820
Door to Floor	mm	640	780	780	830	920	640	780	780
POWER									
Drive Motor	kW	-	0.75	1.1	1.5	2.2	-	0.75	1.1
Fan Motor	kW	0.75	1.1	1.5	2.2	3	0.75	1.1	1.5
Electric Heating	kW	-	-	-	-	-	15.7	37.8	50.4
CONNECTIONS									
Compressed Air	mm	-	8	8	8	8	-	-	-
Steam Inlet	mm	20	25	25	25	40	-	-	-
Discharge Duct	mm	200	250	300	300	310	200	250	300
MACHINE DIMENSIONS									
Width	mm	860	1150	1400	1500	1630	860	1150	1400
Depth	mm	1065	1505	1600	1780	1930	1065	1505	1600
Height	mm	1710	2020	2220	2400	2650	1710	2020	2220
WEIGHT									
Net Weight	kg	350	750	900	1200	1400	350	750	900
Gross Weight	kg	370	785	950	1265	1485	370	785	950
PREESURE									
Steam	Mpa	0.4 - 1.0	0.4 - 1.0	0.4 - 1.0	0.4 - 1.0	0.4 - 1.0	-	-	-
Compressed Air	Mpa	-	0.3 - 0.6	0.3 - 0.6	0.3 - 0.6	0.3 - 0.6	-	-	-
COMSUMPTION *									
Steam	kg / hr	32	63	105	147	210	-	-	-
Electricity	kW / hr	1.2	2.3	2.7	3.1	5.3	17	40	52
OPTIONS									
Stainless Steel Panels		-	+	+	+	+	-	+	+
Cooling Air bypass System		-	+	+	+	+	-	-	-

+: Available on request -: Not applicable

WE RESERVE THE RIGHT TO UPDATE THE ABOVE SPECIFICATIONS WITHOUT NOTICE
* May vary depend on conditions

YOUR LOCAL SAILSTAR DISTRIBUTOR

© Shanghai Sailstar Machinery Group CO., Ltd.

SAILSTAR

Address: 1 Fengpu Ave. Fengpu Industrial Zone,
Shanghai China 201400.

Phone : 86-21-67100168 Fax : 86-21-67100337
Email : info@sailstar.com.cn URL : www.sailstar.com.cn

SAILSTAR USA OFFICE

Address: 2307-A Distribution Center Drive, Charlotte, NC 28269, USA.

Phone: 00-1-704-393-2452

Fax: 00-1-704-393-3257