

HARD MOUNT WASHER EXTRACTORS



HM9 HM13

HM17 HM23



FEATURES:

- Solid and heavy duty structural design
- Frequency inverter drive up to 200G extract
- High quality stainless steel basket and outer shell
- Fully programmable computer control up to 15 wash programs
- Programmable water levels and water temperatures
- Programmable wash, distribution and extract speeds
- Patented safety door interlock system
- All electromagnetic operated valves eliminate need of compressed air
- Stainless steel panels on front panel
- Stainless steel door with large sight glass
- Three flushable compartment dry supply injector
- Standard hot and cold water inlets
- Direct steam injection heating or electrical heating

TECHNICAL DATA

	UNIT	HM9		HM13		HM17		HM23	
Capacity	KG	9		13		17		23	
Heating Mode		Steam	Electric	Steam	Electric	Steam	Electric	Steam	Electric
DRUM									
Volume	L	92		127		170		227	
Diameter	mm	540		540		706		706	
Depth	mm	400		555		435		580	
DOOR									
Door Opening	mm	300		300		400		400	
Door to Floor	mm	300		300		332		332	
SPEED (ADJUSTABLE)									
Wash	RPM	53		53		46		46	
Distribution	RPM	93		93		81		81	
Low Extract	RPM	400		400		350		350	
High Extract	RPM	814		814		712		712	
POWER									
Motor	kW	0.55		1.1		1.5		2.2	
Inverter	kW	0.75		1.5		2.2		3.7	
G-FORCE									
High Extract	G	200		200		200		200	
CONNECTIONS									
Water Inlet	DN	20		20		20		20	
Steam Inlet	DN	15		15		15		15	
Drain Connection	DN	76		76		76		76	
MACHINE DIMENSIONS									
Height	mm	1100		1100		1348		1348	
Width	mm	680		680		870		870	
Depth	mm	840		995		925		1065	
MACHINE WEIGHT									
Net Weight	kg	210		250		395		475	
CONTROLS									
Micro-computer Control		Yes		Yes		Yes		Yes	
DETERGENT SUPPLY									
Dry Supply Compartments		3		3		3		3	
Programmable Signals		3		3		3		3	
PRESSURE									
Steam	Mpa	0.4 - 0.6		0.4 - 0.6		0.4 - 0.6		0.4 - 0.6	
Water	Mpa	0.25 - 0.6		0.25 - 0.6		0.25 - 0.6		0.25 - 0.6	
COMSUMPTION *									
Steam	kg / hr	6	-	8.7	-	11	-	15	-
Electricity	kW / hr	0.34	4.75	0.49	6.87	0.65	8.9	0.87	12.1
Water	L / hr	129		187		245		331	

+ : Available on request - : Not applicable

WE RESERVE THE RIGHT TO UPDATE THE ABOVE SPECIFICATIONS WITHOUT NOTICE
* May vary depend on conditions

YOUR LOCAL SAILSTAR DISTRIBUTOR

© Shanghai Sailstar Machinery Group CO., Ltd.

SAILSTAR

Address : 1 Fengpu Ave. Fengpu Industrial Zone,
Shanghai China 201400.

Phone : 86-21-67100168 Fax : 86-21-67100337

Email : info@sailstar.com.cn URL : www.sailstar.com.cn

SAILSTAR USA OFFICE

Address : 2307-A Distribution Center Drive, Charlotte, NC 28269, USA.

Phone : 00-1-704-393-2452

Fax : 00-1-704-393-3257